



## LED T8 Working Ceiling Lamp

Dimension:



### Specification

| Model No.         | LM-T8CS1812F8-W         | LM-T8NS1812F8-W         | LM-T8WS1812F8-W         |
|-------------------|-------------------------|-------------------------|-------------------------|
| Input Voltage     | AC 100 ~ 265V           | AC 100 ~ 265V           | AC 100 ~ 265V           |
| Rated Power       | 18 W $\pm$ 10%          | 18 W $\pm$ 10%          | 18 W $\pm$ 10%          |
| Usable Lumens     | 2150 lm                 | 1950 lm                 | 1950 lm                 |
| Lumens Efficiency | 120lm/W                 | 110 lm/W                | 110 lm/W                |
| Color Temp.       | 6000 $\pm$ 500 K        | 4000 $\pm$ 500K         | 3000 $\pm$ 500K         |
| CRI               | 80                      | 80                      | 80                      |
| Power Factor      | >0.9                    | >0.9                    | >0.9                    |
| Base              | G13                     | G13                     | G13                     |
| Operating Temp.   | -20°C~40°C              | -20°C~40°C              | -20°C~40°C              |
| Beam Angle        | 140° $\pm$ 10%          | 140° $\pm$ 10%          | 140° $\pm$ 10%          |
| Life Time         | 40000 hrs               | 40000 hrs               | 40000 hrs               |
| Dimensions        | 1253(L)*125(W)*85(H) mm | 1253(L)*125(W)*85(H) mm | 1253(L)*125(W)*85(H) mm |
| Weight            | 2.6kg $\pm$ 20 g        | 2.6kg $\pm$ 20 g        | 2.6kg $\pm$ 20 g        |
| Lens Type         | Foggy                   | Foggy                   | Foggy                   |

#### Remarks

1. The tolerance of luminous flux is  $\pm$ 10%.

2. The dimension tolerance is  $\pm$ 5mm.

3. Laster Tech Corporation LTD. All rights reserved. Product specifications are subject to change without notice.