



# **LED Gas Station Light (80W)**





Embedded type



B type





C-type-

Ceiling type

Pole type

Specification				
Model No.	LOY-LBC80F7-X	LOY-LBD80F7-X	LOY-LBN80F7-X	LOY-LBW80F7-X
Input Voltage	AC100-240V,50/60Hz	AC100-240V,50/60Hz	AC100-240V,50/60Hz	AC100-240V,50/60Hz
Rated Power	80W±10%	80W±10%	80W±10%	80W±10%
Lumens Flux	88001m	8000lm	8000lm	7200lm
Lumens Efficiency	110 lm/W	100 lm/W	100 lm/W	90 lm/W
Color Temp.	6000±500K	5000±500K	4000±500K	3000±500K
CRI	Ra>70	Ra>70	Ra>70	Ra>70
Operating Temp.	-25°C~40°C	-25°C~40°C	-25°C~40°C	-25°C~40°C
Power Factor	>0.9	>0.9	>0.9	>0.9
Life Time	≥ 40000 hrs	≧ 40000 hrs	≥ 40000 hrs	≥ 40000 hrs
Beam angle	60°,90°,120°	60°,90°,120°	60°,90°,120°	60°,90°,120°
Dimensions	343 *343*140 mm	343 *343*140 mm	343 *343*140 mm	343 *343*140 mm
Weight	9.5±1.5 kg	9.5±1.5 kg	9.5±1.5 kg	9.5±1.5 kg

#### Remarks




<sup>1.</sup> The tolerance of luminous flux is ±10%.


<sup>2.</sup>The dimension tolerance is ±5mm.


<sup>3.</sup> The appearance and specifications of the product may be modified for improvement without notice.




## **Light Distribution Curve**










### **Product Introduction**








#### Installation Instruction

#### Mode1:The ceiling type of canopy light installation

- 1. According to the bracket hole distance, fix two M10 screws on the ceiling.
- 2.Put the bracket hole position of screws, then tighten nuts
- 3. Put the lamp on the bracket.
- 4.Link the wire










#### Mode 2: Recessed installation of led canopy light (new building gas station)

- 1. The size of ceiling cut-out is 343\*343, and Measure the wall thickness T
- 2. Adjust the movable screens of lamp to the T height
- 3.Lean the lamp for putting it on the ceiling













#### Mode 3: Recessed installation of led canopy light (old gas station)

- 1. The size of ceiling cut-out is 375\*375.
- 2. Leaning the LED lights into ceiling, on the other side of the hole to connect the AC input wire .
- 3. Fix the installation block on the ceiling with special metal plate and screws, adjust the GAP to T, make it ceiling of clamping hole wall.
- 4. Move the LED lights at the other side to the hole position, installation complete.






#### **Product Details**



·High-performance·LED-and-high-quality-driver-ensure-the-long-life-span-of-the-whole-lamp, and the professional structural design ensures the excellent heat dissipation and IP65 waterproof.

#### **Dimension**





### **Flexible Application**

## A·variety·of·installations·adapt·to·different·








A type

Embedded type

**B** type





C type

Pole type








## Professional light distribution, the best lighting solution

 Unique light distribution design to evenly irradiate the light into the selected vertical and horizontal planes.

Special optical design strengthens the vertical plane of the lighting, and the display effect is greatly increased in fuel meter readings district.

(Traditional lights always tends to downward the light and emphasize on the light of horizontal planes, but ignore the vertical illumination in the working place.)



After customers enter into the gas station, unique asymmetric light distribution design of lighting can be effectively concentrated on the working area of the gas station, greatly improve the utilization rate of light as well as the brand image of the gas station.

 Excellent resistance to stun design will ensure that the drivers won't feel dazzling and discomfort when drive close to the gas station, so the safty has been improved greatly.



