




18W LED Down Light (Square)

Dimension:



Specification


Model No.	LOR-DLC216S18F8	LOR-DLN216S18F8	LOR-DLW216S18F8
Input Voltage	AC100-240V		
Rated Power	18W	18W	18W
Luminous Flux	1530lm	1440lm	1350lm
Luminous Efficiency	85 lm/W	80 lm/W	75 lm/W
Color Temperature (CCT)	6000±500K	4000±500K	3000±500K
CRI	Ra80		
Working Temperature Rang	-20°C~ +40°C		
Power Factor	>0.9		
Life Time	≥ 40000 hrs		
Beam angle	110°		
Cut-out	158mm		
Dimensions /Weight	172.0 *172.0*33.0 mm / 460±20 g		
LED driver	Fixed output		
Materials and Finishing	PC diffuser with high light transmission, High reflectance aluminum reflector (White Color)		

Remarks


- 1.The tolerance of luminous flux is ±10%. 2.The dimension tolerance is ±5mm.
- 3.The appearance and specifications of the product may be modified for improvement without notice.
- 4.All parameters of products are based on the measurement of Laster Tech laboratory.

Laster Tech Corporation LTD. Building F No.4,Minxiang St., Zhonghe City, Taipei County 235, Taiwan V1.0


LUMINOUS INTENSITY DISTRIBUTION



照度距离曲线/Illumination distance curve



Installation Instruction



Product Package

Packing	Dimension(mm)	Quantity(pcs)	Net Weight(kg)	Gross Weight(kg)
Large Carton	560*275*525	30	13.80	20.13